



KARPEX

Multi-Use Carpet Cleaner

DESCRIPTION

Karpex multi-purpose carpet cleaner is a unique product formulated for commercial carpet cleaning that does the work ordinarily requiring several products. It combines modern surfactants and water miscible solvents for the optimum in it's ability to penetrate, suspend and remove imbedded dirt and greasy, oily soil.

BENEFITS

SUPERIOR CLEANING: Far superior to other carpet cleaners in removing greasy, oily soil and caked in dirt from carpets in restaurants, offices, manufacturing plants, etc.

MULTI-PURPOSE: Karpex by itself can replace spotters, pre-sprays, mop on cleaners, extraction cleaners and bonnet cleaners, while also doing a better job.

FASTER CLEANING/FASTER CLEAN-UP: The Karpex formula works faster in cleaning the carpet and because greasy, oily soil is emulsified it rinses quickly from the equipment used.

HOW TO USE

ASA SPOTTER: Dilute 1 part Karpex with 4 parts of water. Apply with a cloth or sprayer. Blot with a clean white cloth. When rubbing, work from the outer edge of spot towards its center. Change to clean part of cloth as needed.

ASA A TRAFFIC LANE PRE-SPRAY: Dilute 1 part Karpex with 8 parts of water (1 pint per gallon). Spray solution in a wet mist to dampen soiled area. Where soil is heavy, brush into pile. Allow to sit a few minutes before proceeding with cleaning.

FOR HOT WATER EXTRACTION: Add 1 to 2 ounces of Karpex (depending on level of soil) to each gallon of water in solution tank.

FOR BONNET OR SPIN DRY USE: Dilute 1 part Karpex with 8 parts of water (1 pint per gallon). Spray a fine mist over a small area of carpet and over bonnet. Place bonnet under a rotary floor machine and buff carpet to clean. Rinse or change the bonnet as needed.

NOTE: Before using any chemical on carpet, always test in an out of sight spot for color fastness.



SPECIFICATIONS

APPEARANCE.....	Straw colored liquid
ODOR.....	Non-specific
SPECIFIC GRAVITY.....	1.040 ± 0.005
DENSITY.....	8.68 ± 0.05 lb/gal
BOILING POINT.....	Near 212°F
FLASH POINT.....	None to boiling
STABILITY.....	One year minimum
pH.....	13.3

*** NOT FOR USE ON WOOL CARPETS**

PRODUCT CODE.....KAR

TrueKleen Products is a division of The Bullen Companies, Folcroft, PA 19032
Phone 610-534-8900 • Fax 610-534-8912 • www.bullenonline.com